

用紙 第 1 頁 共 10 頁

[illegible]

用紙 第二頁共10頁

```
public class Foo {  
    public static void main(String[] args) {  
  
  
  
  
  
  
  
  
    }  
}
```


4. What is the output of the following code. (12 points)

```
public class Foo {  
    public static void main(String[] args) {  
        int i=2;  
  
        switch (i) {  
            case 0:  
                System.out.print("Ilan ");  
  
            case 1:  
                System.out.print("JiaoShi ");  
  
            case 2:  
                System.out.print("Fo ");  
  
            case 3: word="Guang";  
                System.out.print("Guang ");  
  
            default:  
                System.out.println("University.");  
        }  
    }  
}
```


不可使用計算機、電子字典及手提電腦等電子產品！

5. What is the output of the following program? (12 points)

```
public class Foo {
    public static void main(String[] args) {
        int i=1;

        for (int i=1; i<3; i++) {
            // wasting time.
        }

        System.out.print("Fo Guang is the ");

        switch (i) {
            case 1:
                System.out.println("First!");
                break;

            case 2:
                System.out.println("Second!");
                break;

            case 3:
                System.out.println("Third!");
                break;

            default:
                System.out.println("Last!");
        }
    }
}
```


6. Finish the definition of the class Foo so that it can work with the interface Welcome properly. (8 points)

```
public interface Welcome {
    public void sayHello();
}
```

```
public class Foo implements Welcome {
    public static void main(String[] args) {
```

```
        Foo foo=new Foo();
```

```
        foo.sayHello();
```

```
    }
```

```
}
```


用紙 第8頁共10頁

不可使用計算機、電子字典及手提電腦等電子產品！

用紙 第 9 頁共 10 頁

```
public class Foo {
    public static void main(String[] args) {
        for (int i=0; i<args.length; i++) {
            System.out.println(args[i]);
        }
    }
}
```

[illegible]

不可使用計算機、電子字典及手提電腦等電子產品！

10. Fill in the output of the following code. (10 points)

```
public class Foo {
    public boolean isOdd(int i) {
        return ((i%2)==1);
    }

    public static void main(String[] args) {
        int[] test={0, 1, -1};
        Foo foo=new Foo();

        for (int i=0 ; i<test.length ; i++) {
            System.out.println("isOdd("+test[i]+")"+foo.isOdd(i));
        }
    }
}
```


}

[illegible]

3

```
int main( )
{
}
}
```

節光人文社會學院九十五學年度碩士班招生考試試題卷

系所別：資訊學系碩士班

科目：程式設計 (C++)

用紙 第2頁共9頁

3. Rewrite the following multiway if-else statement with one switch statement. (12 points)

```
#include <iostream>
using namespace std;
int main()
{
    char ch = 'm';
    if (ch == 'D' || ch == 'd')
        cout << "Dell" << endl;
    else if (ch == 'M' || ch == 'm')
        cout << "Microsoft" << endl;
    else if (ch == 'I' || ch == 'i')
        cout << "Intel" << endl;
    else
        cout << "Unknown" << endl;
    return 0;
}
```

int main()

{

}

不可使用計算機、電子字典及手提電腦等電子產品！

僑光人文社會學院九十五學年度碩士班招生考試試題卷

系所別：資訊學系碩士班

科目：程式設計 (C++)

用紙 第3頁共9頁

4. Rewrite the following switch statement with one multiway if-else statement. (12 points)

```
#include <iostream>
```

```
using namespace std;
```

```
int main( )
```

```
{
```

```
    int number = 5;
```

```
    switch (number)
```

```
    {
```

```
        case 1:
```

```
        case 3: cout << "Odd" << endl; break;
```

```
        case 2:
```

```
        case 4: cout << "Even" << endl; break;
```

```
        default: cout << "Unknown" << endl; break;
```

```
    }
```

```
    return 0;
```

```
}
```

```
int main( )
```

```
{
```

```
}
```

5. What is the output of the following program? (12 points)

```
#include <iostream>
using namespace std;
int main()
{
    int i;
    const int arraySize = 3;
    int array[arraySize];
    int *ip1, *ip2;
    ip1 = array;
    ip2 = new int[arraySize];
    for (i = 0; i < arraySize; i++)
    {
        array[i] = i + 1;
        ip2[i] = i + 4;
    }
    for (i = 0; i < arraySize; i++)
        cout << ip1[i] << " ";
    cout << endl;
    for (i = 0; i < arraySize; i++)
        cout << *(ip2 + i) << " ";
    cout << endl;
    for (i = 0; i < arraySize; i++)
        array[i] += ip2[i];
    for (i = 0; i < arraySize; i++)
        cout << *(ip1 + i) << " ";
    cout << endl;
    for (i = 0; i < arraySize; i++)
        cout << ip2[arraySize - 1 - i] << " ";
    cout << endl;
    return 0;
}
```


6. What is the output of the following program? (8 points)

```
#include <iostream>
using namespace std;
template<class T>
void swapValues(T& v1, T& v2)
{
    T temp;
    temp = v1;
    v1 = v2;
    v2 = temp;
}
int main()
{
    int one = 3, two = 7;
    double three = 4.4, four = 8.8;
    char five = 'x', six = 'y';
    long seven = 128, eight = 821;
    swapValues(one, two);
    cout << one << " " << two << endl;
    swapValues(three, four);
    cout << three << " " << four << endl;
    swapValues(five, six);
    cout << five << " " << six << endl;
    swapValues(seven, eight);
    cout << seven << " " << eight << endl;
    return 0;
}
```


7. What is the output of the following code? (8 points)

```
#include <iostream>
#include <cmath>
#include <cstdlib>
using namespace std;
int main()
{
    double x = 4;
    double y = 2;
    double z = -2.7;
    double w = 3.1;
    cout << sqrt(x) << " " << pow(x, y) << endl;
    cout << fabs(z) << " " << fabs(w) << endl;
    cout << floor(z) << " " << floor(w) << endl;
    cout << ceil(z) << " " << ceil(w) << endl;
    return 0;
}
```


8. What is the output of the following code? (10 points)

```
#include <iostream>
using namespace std;

class DayOfYear
{
public:
    DayOfYear(int monthValue, int dayValue)
        : month(monthValue), day(dayValue) { };
    DayOfYear() : month(1), day(1) { };
    void output();
private:
    int month;
    int day;
};
```



```
int main()
{
    const int size = 5;
    DayOfYear dataPoint[size];
    int i;
    for (i = 0; i < size; i += (size - 1))
    {
        cout.width(2);
        cout << i;
        dataPoint[i].output();
    }
    for (i = 0; i < size; i++)
        dataPoint[i] = DayOfYear(i, 2 * i);
    for (i = 0; i < size; i += 2)
    {
        cout.width(2);
        cout << i;
        dataPoint[i].output();
    }
    return 0;
}

void DayOfYear::output()
{
    cout.width(3);
    cout << month;
    cout.width(3);
    cout << day << endl;
}
```


嘉應州社會學院九十五學年度碩士班招生考試試題卷

系別：資訊學系碩士班

科目：程式設計 (C++)

用紙 第8頁共9頁

9. What is the output of the following program? (8 points)

```
#include <iostream>
#include <vector>
using namespace std;
int main()
{
    vector<int> v(3);
    cout << v.size() << endl;
    v[0] = 1;
    v[1] = 2;
    for (int i = 0; i < v.size(); i++)
        cout << v[i] << " ";
    cout << endl;
    v.push_back(3);
    v.push_back(4);
    cout << v.size() << endl;
    for (int j = 0; j < v.size(); j++)
        cout << v[j] << " ";
    cout << endl;
    return 0;
}
```


10. Fill in the output in the following Sample Dialogue. (10 points)

```
#include <iostream>
using namespace std;
int main()
{
    int *p1, *p2, *p3, *p4, n1, n2;
    n1 = 4;
    n2 = 8;
    p1 = &n1;
    p2 = &n2;
    p3 = &n1;
    p4 = &n2;
    p1 = p2;
    *p3 = *p4;
    n2 = 6;
    cout << n1 << " " << n2 << endl;
    cout << p1 << " " << p2 << endl;
    cout << p3 << " " << p4 << endl;
    cout << *p1 << " " << *p2 << endl;
    cout << *p3 << " " << *p4 << endl;
    cout << &(*p1) << " " << &(*p3) << endl;
    return 0;
}
```

Sample Dialogue

0	0	1	2	F	F	6	C		0	0	1	2	F	F	6	8			